


Bottle Cooler Key Features

Designed for stylish, effective storage and display of bottles and cans for easy customer selection



01. Fitted with anti-condensation double glazed Argon gas glass door with aluminium alloy frame
02. Bright low energy LED with on / off switch for excellent product display and easy customer selection
03. Engineered with hidden condensing unit to fit with interior design and minimising the requested installation space
04. Fully adjustable perforated 304 grade stainless steel shelves. Accommodates a vertical stacking capacity of three or six levels of 10" bottles
05. Excellent thermal efficiency, high density polyurethane insulation with Zero ODP (Ozone Depletion Potential) and Low GWP (Global Warming Potential)
06. Removable magnetic door gasket with air release points provides an excellent seal to prevent heat ingress
07. BC1, BC2 and BC3: 10Hmm levelling feet at front to ensure stability on an uneven floor and 15Hmm castors at rear
08. BC95 and BC200: 10Hmm levelling feet to ensure stability on an uneven floor
09. Forced air refrigeration system ensures effective air circulation
10. Imported, durable and energy-efficient compressor
11. Condenser and evaporator with Hydrophilic aluminium fins provides high corrosion resistance properties
12. Accurate helium leak detection system ensures the quality of the entire refrigeration system
13. Automatic defrost ensures the evaporator working to its optimum performance
14. Automatically vaporises defrost water, drainage is not required
15. Designed and engineered to operate up to 32°C ambient
16. Environmental-friendly CFC-free refrigerant (R134a)
17. HACCP compliant

Wall Mounted Bottle Cooler

Specification

- Foodsafe 304 grade stainless steel exterior (including base) and 304 grade BA mirror stainless steel interior
 - Galvanised steel exterior back
 - Fitted with cylindrical lock
 - With wall mount bracket
-

Options

1. 304 grade stainless steel exterior back
 2. Black colour bond exterior / back
 3. 304 grade stainless steel door
 4. Left-hand-side door hinge
 5. Additional shelving / shelf supporters
 6. 220V / 60HZ / 1PH
-

Product List



Wall Mounted BC Technical Data

Model	BCWM-1	BCWM-2	BCWM-3
Temp Range (°C)	+4 / +10	+4 / +10	+4 / +10
External Dimension (mm)			
Width	600	900	1352
Depth	450		
Height	835		
Internal Dimension (mm)			
Width	530	830	1275
Depth	310		
Height	490		
Thickness of 304 grade stainless steel (mm)			
Exterior	0.7		
Interior	0.7		
Opening Depth	1005	860	
Capacity (cu.ft / litres)	3.5 / 100	5.5 / 155	8.2 / 230
Capacity (cans @ 330ml)	96	120	180
Power Supply	220V / 50HZ / 1PH		
	13 amp plug		
Power Input - Running (amps) *	2		3.5
Rating Power (watts) *	440		770
Compressor (HP)	1/5		1/4
Heat Rejection (watts) (Evaporating at -10°C in 32°C ambient)	287		485
Refrigerant	R134a		
Standard fittings			
Stainless steel perforated shelves	2		6
Shelf supporters	8	12	24

* 20% increase for 60HZ power supply