

## Table Top



**TT-3500D**



**TTD-3500D**

## Built-In



**BI-3500D**



**BID-3500D**

## Table Top & Built-in Wok



**TTW-3500D**



**BIW-3500D**

Model	Dimension (L x W x H mm)		Voltage	Power	CE Approval
	Overall	Ceran Glass			
TT-3500D	328 x 475 x 110	273 x 273 x 4	230V/50-60Hz/1PH	3.5kW x 1	✓
TTD-3500D	400 x 740 x 196	350 x 550 x 6	230V/50-60Hz/1PH	3.5kW x 2	✓
TTW-3500D	385 x 480 x 160	dia. 311 x 70	230V/50-60Hz/1PH	3.5kW x 1	✓
BI-3500D	360 x 380 x 81	360 x 380 x 4	230V/50-60Hz/1PH	3.5kW x 1	✓
BID-3500D	450 x 700 x 156	350 x 550 x 6	230V/50-60Hz/1PH	3.5kW x 2	✓
BIW-3500D	385 x 385 x 130	dia. 311 x 70	230V/50-60Hz/1PH	3.5kW x 1	✓

## Compact Design

Units are downsized by 20%-50% compare to previous models, much smaller and lighter.

## IR & NTC Dual Sensor

Better temperature control thanks to fast responding IR sensor.

## Better performance

Improved performance on heat dissipation and enhanced stability to power voltage change.

Simple to service with an integrated PCB.

## Energy Saving

Standby power of D series is only 1 watt.

## Automatic Safety Shut-off

Automatically shut-off when left on for more than 60 seconds without a pan or with an incompatible pan.

## Overheating Protection Device

If pan temperature reaches above 250°C for 60 seconds, the unit will automatically shut-off.

## Variable Power Range Control

Power level from 1-12.

## 袖珍設計

比上一代細小和輕巧約20%~50%，容易安裝及輕易移動爐具。

## 紅外線和熱敏電阻雙重感應器

裝有紅外線和熱敏電阻感應器，能夠更快速準確地檢測溫度。

## 提升效能

改良散熱效能，增強對電壓變化的穩定性。只有一塊綜合電子板，方便維修。

## 環保省電

待機電力只需要 1 瓦，高效省電。

## 自動鍋具感應

當電磁爐感應不到適合的鍋具超過60秒，電磁爐便會自動關機。

## 過熱保護裝置

當鍋具達到250°C並超過60秒，電磁爐便會自動關機。

## 多段火力調控

設有十二段火力調控。

## Additional Features / 附加功能：

Emergency Stop Button  
緊急停止按鈕  
(Built In Hob Only)



Removable Air Filter  
可拆式空氣過濾網  
(Tabletop Hob Only)



## Accessories / 配件：

Induction Wok Pan  
電磁感應鍋  
(For Table Top & Built-in Wok)

