

PRECISE

Table-Top Induction Hob

DT-28T & DT-35T

DT-28T DT-35T



Accessories:

RF Wireless Temperature Probe measuring food core temperature and pairing with DT-35T.



Model 型號	DT-28T	DT-35T
Electrical Requirement 供電要求	230V/50-60Hz/1PH; 2.8kW	230V/50-60Hz/1PH; 3.5kW
Fuse Rating 保險絲	13Amp	16Amp
Overall Dimension 基本尺寸	328 (W) x 475 (D) x 110 (H) mm	328 (W) x 475 (D) x 110 (H) mm
Glass Dimension 玻璃面尺寸	73 (W) x 273 (D) x 4 (H) mm	273 (W) x 273 (D) x 4 (H) mm
Power Level 火力調控段數	11	12
CE Approval	✓	✓

Features:

Compact Design

Much smaller and lighter.

IR & NTC Dual Sensor

Better temperature control thanks to fast responding IR sensor.

Low Temperature Cooking Function

With precise temperature holding function, 24 hour timer and temperature setting at 40°C-220°C of 5 °C interval.

Better Performance

Improved performance on heat dissipation and enhanced stability to power voltage change.
Simple to service with an integrated PCB.
Removable air filter.

Energy Saving

Standby power of D series is only 1 watt.

Automatic Safety Shut-off

Automatically shut-off when left on for more than 60 seconds without a pan or with an incompatible pan.

Overheating Protection Device

If pan temperature reaches above 250°C for 60 seconds, the unit will automatically shut-off.

特點:

袖珍設計

細小輕巧，容易安裝。

紅外線和熱敏電阻雙重感應器

裝有紅外線和熱敏電阻感應器，能夠更快速準確地檢測溫度。

低溫烹調功能

具有保溫功能和24小時計時器，溫度範圍為攝氏40度至220度，每5度可調，適合低溫烹調。

提升效能

改良散熱效能，增強對電壓變化的穩定性。
只有一塊綜合電子板，方便維修。
備有可拆式空氣過濾網。

環保省電

待機電力只需要1瓦，高效省電。

自動鍋具感應

當電磁爐感應不到適合的鍋具超過60秒，電磁爐便會自動關機。

過熱保護裝置

當鍋具達到250°C並超過60秒，電磁爐便會自動關機。

C.E.C.

酒店設備有限公司

C.E.C. CATERING EQUIPMENT CO., LTD.

6/F., Unify Commercial Industrial Building, 31 Tai Yip St., Kwun Tong, Kowloon, Hong Kong

Tel.: (852) 2757 3410 Fax: (852) 2796 1523 email: info@cechk.com website: www.cechk.com